



## Finma-Sil 20MG

### Description

Finma-Sil 20MG is characterized by a very broad compatibility in most aqueous systems, including acrylate and polyurethane dispersions.

The amount of wetting agents is reduced to a minimum. Finma-Sil 20MG has a pronounced high matting efficiency. It does not tend to cream even after prolonged storage and does not sediment. Finma-Sil 20MG can be processed excellently and is pumpable.

Finma-Sil 20MG differs from Finma-Sil 20P in giving a smoother surface and better mechanical resistance.

### Range of use

- Water-based coatings (1pack/2pack)
- UV-coatings (100%, water-based)

### Applications

- Parquet varnishes
- Furniture coatings/foils
- Foil coatings
- Plastic part coatings
- Glass coatings
- Packaging inks

### Specification

Solid content	20 ± 1%
Dispersing fineness	≤ 20 µm

### Typical properties

general information, not part of the specification

Appearance	white paste
Density	1.09 g/cm <sup>3</sup>
pH-value	neutral

### Packaging

Packaging unit	25 kg plastic drum 100 kg plastic drum 1000 kg container (IBC)
----------------	--



## Finma-Sil 20MG

### Storage

Store in closed containers at low relative humidity and protected from freezing. Always keep the containers closed. The storage period of six months after shipment should not be exceeded.

It is recommended to homogenize by stirring before use.

This datasheet should advise technically. It is not binding and does not claim to be complete.

The above data do not represent a characteristic warranty. The customer is not freed by this product information from his obligation to the examination on suitability for the intended purposes and procedures. Same applies to the inspection of incoming goods at the customer.

created: 2018-10-02

replaces sheet from: 2018-07-25

